











SYSTEM ACCESSORIES

NPTF Fittings & Oil




System Accessories

Model	Description	Model	Description
 F1	Hex Nipple 3/8" M NPTF Threads	 F10	Reducer Fitting 3/8" M to 1/4" F NPTF Threads
 F3	3" Nipple 3/8" M NPTF Threads	 F11	Tee 3/8" F NPTF Threads
 F6	6" Nipple 3/8" M NPTF Threads	 F13	Coupling 3/8" F NPTF Threads
 F7	90° Elbow 3/8" F NPTF Threads	 F15	Cross Fitting 3/8" F NPTF Threads
 F9	90° St. Elbow 3/8" M - 3/8" F NPTF Threads	 F17	Reducer Fitting 1/4" M to 3/8" F NPTF Threads

All fittings above are rated for 10,000 psi, and are engraved for added safety and readability.

Gauge Adapter



Model#
GA1
Order#
18977

Gauge Adapter Simplifies Your Connection Point

Simplex Hydraulic Oil

Special, high pressure formulated, premium grade oil for all Simplex hydraulic products. High viscosity index ensures maximum lubricity over a wide range of operating temperatures.



AO1	1 Gallon
AO5	5 Gallons
AO55	55 Gallons

Viscosity Index - 100 Minimum

Vis, Ssu @ 100° F -	150 - 155
Vis, Ssu @ 210° F -	45 - 50
Vis, Ssu @ 0° F -	< 15,000
Pour Point -	-50° F
Flash Point -	400° F
Analine Point -	204.8° F

Includes: Anti-Foam, Anti-Rust And Low Temperature Additives