











Model	Description	Dimensions
 <p>Model# G5 Order# 18905</p>	<ul style="list-style-type: none"> ▶ Liquid filled dampens needle vibration. ▶ Reads both PSI and Bar ▶ 1% full scale accuracy. ▶ 500 psi increment up to 10,000 PSI ▶ Stainless steel casing. 	 <p>2.50" .56" Square 1/4" NPT</p>
 <p>Model# G6 Order# 18906</p>	<ul style="list-style-type: none"> ▶ 10,000 psi to 15,000 psi warning zone. ▶ The calibrated scale reads from 0-10,000 psi ▶ Reads both PSI and Bar ▶ Liquid filled dampens needle vibration. ▶ 1% full scale accuracy. ▶ Large easy to read 4" face. ▶ Rubber blowout plugs for safety. ▶ Stainless steel casing. 	 <p>4.00" .78" Hex 1/4" NPT</p>
 <p>G7</p>	<ul style="list-style-type: none"> ▶ 10,000 psi to 15,000 psi warning zone. ▶ The calibrated scale reads from 0-10,000 psi ▶ Reads both PSI and Bar ▶ Liquid filled dampens needle vibration. ▶ 1% full scale accuracy. ▶ Large easy to read 4" face. ▶ Standard on all Simplex Torque Wrench Pumps. 	 <p>4.00" 1/4" NPT</p>
 <p>GD1</p>	<ul style="list-style-type: none"> ▶ Designed for high cycle pressure applications ▶ Self powered Lithium batteries. ▶ Full 4 digit display. ▶ + / - .25% full scale accuracy. ▶ 10 million cycle life minimum. ▶ Stainless steel sensor that is vibration & shock resistant. ▶ The calibrated scale reads from 0-10,000 psi 	 <p>2.66" .62" NPT</p>
 <p>GD2</p>	<ul style="list-style-type: none"> ▶ .75" characters and 270° bar graph "analog" readout. ▶ Splash proof phenolic housing. ▶ + / - .25% full scale accuracy. ▶ Keypad enable/disable of peak high or peak low hold. ▶ Stainless steel sensor that is vibration & shock resistant. ▶ The calibrated scale reads from 0-10,000 psi 	 <p>5.45" 1.33" .87" Flats 1/4" NPT</p>

System Accessories

SCALED TONNAGE GAUGES FOR SIMPLEX CYLINDERS

Model	Cylinder Tonnage	Face Diameter	Applicable Cylinder Series
GT5	5, 10, 15	4"	R5, R10, R15, RFS10, RLS101, RDA1010
GT20	20, 50	4"	RLS201, RLS502, RLS1002, RFS20, RFS50, RFS100
GT25	25, 55, 100	4"	R25, R55, RDA55, R100
GT30	30, 50, 100	4"	R308, RLS302, RFS30, RLN30, RLN50, RLN100, RLR306, RLR50, RLR100
GT100	150, 200	4"	RDA100, RDA200, RFS150, RLN150, RLN200, RLR150, RLR200
GT150	100, 150, 200	4"	RDA150
GTH12	12, 20, 30	4"	RC12, RC20, RC30, RCD30
GTH60	60, 100, 150	4"	RC60, RC1003, RCD6010, RCD100, RCD1505

