

"X200B"  
Technical Data



#### Frequency band

315 / 418 / 429 / 433 / 447 /  
470 / 868 / 915 MHz / 2.4 GHz

#### Number of functions

up to 3 on/off + EMO

#### Power supply

24~48V / 90~460V AC / DC

#### Stop/Safety contact rating

6A

#### Command contact rating

5A (250V AC)

#### Command response time

~ 25 ms

**Safety category for the  
Stop protection (EN ISO 13849-1)**  
PL d (optional)

#### Operating and storage temperature

(-20°C)~(+55°C) / (-40°C)~(+65°C)

#### Protection degree

IP65

#### Housing material

PA6 (GF30%)

- Status LED
- Internal BootLoader,  
up firmware to the date  
by using computer
- Wireless pairing to transmitter

#### Weight

approx. 2950g

#### Size

122×86×34mm

#### Antenna

Internal  
SMA External  
SMA 2M / 5M cable magnetic





### So Mini, so Lightweight

Due to its small size, you can install it easily and need not too much space.

### Pretend to be Wireless

It can be connected with the wire through the hole at the back of the device.



“X200B practical usage”

### Considerate Buttons

You can operate the receiver directly without the transmitter — just push the buttons on the receiver. Moreover, it can be operated simultaneously by two people.

